

10/030335

JC10 Rec'd PCT/PTO 13 NOV 2001

## Claims

1. A wiper system (10) for motor vehicles, in which at  
5 least one wiper arm (36) with a wiper blade (38) of a windshield  
wiper (12, 14) is placed in a parked position (26) parallel to a  
lateral boundary (40, 46) of a vehicle window (16), characterized  
in that the wiper arm (36) with the wiper blade (38) in the  
parked position (26) is disposed between the vehicle window (16)  
10 and a cover trim (34, 48) extending at a spacing distance (56)  
from the window.

2. The wiper system (10) of claim 1, characterized in that  
the cover trim (34) is formed onto a column (40) of the vehicle  
15 body adjoined by the vehicle window (16).

3. The wiper system (10) of [one of the foregoing claims]  
claim 1, characterized in that the cover trim (48) is formed at  
least in part by a plastic trim.

20 4. The wiper system (10) of [one of the foregoing claims]  
claim 1, characterized in that the wiper arm (36) with the wiper  
blade (38) in the parked position (26) is covered toward the  
passenger compartment by a black coloring (44) on the periphery  
25 of the vehicle window (16).

5. The wiper system (10) of [one of the foregoing claims]  
claim 1, characterized in that the wiper blade (38) in the parked  
position (26) largely closes off the opening (60) between the  
30 cover trim (34, 48) and the vehicle window (16).

6. The wiper system (10) of claim 5, characterized in that

the wiper blade (38), on the side remote from the vehicle window (16), has a seal (52, 54), which in the parked position (26) adjoins the cover trim (34, 48).

5           7. The wiper system (10) of claim 6, characterized in that the seal is embodied as a spoiler (54).

10          8. The wiper system (10) of [one of the foregoing claims] claim 1, characterized in that the wiper arm (36) is embodied as a leaf spring wiper arm and/or the wiper blade (38) is embodied as a flat-bar wiper blade.

15          9. The wiper system (10) of [one of the foregoing claims] claim 1, characterized in that a reversing motor is provided, which reaches the upper turning position (32) of the wiper arm (36) a few degrees before the parked position (26).

20          10. The wiper system (10) of claim 9, characterized in that the reversing motor can move to a service position (30), which is located approximately in the middle of the vehicle window (16).